



Features:

- R-410A refrigerant
- Compact design
- Low noise level
- 4-Way air flow
- Removable corner cap for easy maintenance
- LCD display
- Internal water drainage pump

Fan Coil Unit | 60 HZ
B Series Cassette



Technical Specifications:

REFRIGERANT R-410A

Ceiling Cassette Unit						
Model		TBK41B-018-3L1C	TBK41B-024-3L1C	TBK41B-036-3L1C	TBK41B-048-3L1C	TBK41B-060-3L1C
Cooling	Btu/H	18,000	24,000	36,000	48,000	60,000
Air Flow Volume (m³/h)	High	900	1200	1580	1700	2400
	Medium	650	950	1200	1300	2150
	Low	490	510	860	970	1930
Noise Level dB (A)	High	42	51	52	52	55
	Medium	40	45	48	48	52
	Low	38	31	41	41	49
Power Supply	V/PH/Hz	208-230/1/60				
Unit Dimension (WxHxD)						
Net Dimension	mm	570x255x570	840x230x840	840x305x840	840x305x840	960x285x960
Packing Dimension	mm	710x310x710	950x345x940	950x415x940	950x415x940	1040x305x1040
Panel Dimension (WxHxD)						
Net Dimension	mm	650x30x650	953x40x953	953x40x953	953x40x953	1140x45x1140
Packing Dimension	mm	760x100x760	1030x135x1030	1030x135x1030	1030x135x1030	1195x100x1195
Weight						
Net Weight of Indoor Unit	kg	23	27	33	33	40
Net Weight of Indoor Unit Panel	kg	2	6	6	6	8
Connectivity Pipe Diameter (Liquid)	inches	1/4"	3/8"	3/8"	3/8"	3/8"
Connectivity Pipe Diameter (Gas)	inches	1/2"	5/8"	3/4"	3/4"	3/4"
Max.Refrigerant piping Length	mm	25	30	30	50	50
Max.Vertical Separation	mm	10	15	15	30	30

Authorized Dealer: